



SUPRA 560

**A breakthrough in performance
and reliability for small to
medium-sized trucks.**



PERFORMANCE SPECIFICATIONS

SUPRA 560

Supra 560 is specifically designed for the safe, reliable transport of perishable and frozen food.

Supra 560 offers proven reliability, low noise, and the best overall performance wrapped in a sleek aesthetic design.

- **Exceptional reliability** ensures the lowest overall cost to operate.

- **Extended service intervals** for maximum asset utilization.

- **Low-noise operation** so that you can operate at all hours.

- **High capacity and airflow** for maximum product protection.

- **Microprocessor controls** that are powerful yet easy to operate.

Accessories and Options:

- Battery (dealer-supplied)
- Battery box
- 30-gallon fuel tank
- 50-gallon fuel tank
- Fuel heater
- Top debris protection grille
- Supply-air control
- Stealth noise reduction kit
- Host system door shutdown switch
- Water and electric heat systems



Condenser Dimensions

71.7" x 31.1" x 21.8"
(1,823 x 791 x 555 mm)

Evaporator Dimensions

48.2" x 21.6" x 11.4"
(1,225 x 550 x 290 mm)

Body Opening

49.0" x 12.2"
(1,245 x 310 mm)

Approximate Weights:

TDB-13: 806 lb (365 kg) without standby
TDS-13: 850 lb (385 kg) with standby

Cooling/Temperature Capacity:

Ambient at 100°F (38°C)

Speed: 2,300 rpm diesel/60-hertz electric operation

Evaporator Return Air Temp.	Diesel Operation		Standby Operation	
	Btuh	Watts	Btuh	Watts
35°F (2°C)	14,500	4,250	14,000	4,100
0°F (-18°C)	8,500	2,490	8,500	2,490
-20°F (-29°C)	5,000	1,465	4,500	1,320

Standard Features Include:

- CT2-29 TriVortex diesel engine
- 05K12 2-cylinder compressor
- Long life spin-on lube oil filter
- Long life maintenance-free evaporator fan motors
- Automatic hot-gas heating system
- Refrigerant R-404A
- Three-way refrigeration valve system
- Standard with electric standby (model TDS)
- Heavy-duty electric standby motor: 208v/230v-3ph-60Hz
- Remote-mount power receptacle
- Microprocessor control system
- CAB COMMAND™ remote control center
- Critical Cargo Monitor (in cab)
- Audible temperature alarm (in cab)
- Red light visual warning alarm (in cab)
- Automatic pretrip system
- Lighted CAB COMMAND keys
- Main on/off system power switch
- Display indicators
 - Cool-Heat-Defrost
 - Start/Stop-Out of Range
 - Engine Operation-Electric Standby
- Digital readout
- CAB COMMAND (in cab)
- Engine coolant temperature
- Unit suction pressure
- Battery voltage
- Engine run hours

Standard Features (continued):

- Electric standby hours
- Maintenance interval hours
- Total on-time hours
- Setpoint temperature
- Box return-air temperature
- Automatic Start/Stop fuel saver
- City Speed control
- Automatic defrost control
- Extended-life antifreeze
- High coolant temperature protection
- High-power 70-amp alternator
- Heavy-duty dry air cleaner
- Low engine oil protection
- High refrigerant pressure protection
- Low refrigerant pressure protection
- Receiver tank pressure relief
- Bottom panel
- Installation package
 - Electric fuel pump
 - Fuel lines
 - Battery cables
 - Installation hardware
 - Fuel tank pickup tubes

Specifications are subject to change without notice.

Warranty: Product warranty and limitations are outlined in Form 62-10857. This warranty applicable only in North America. Consult your Carrier Transicold representative for warranty coverage elsewhere. Form 62-11659.

North America
Carrier Transicold
700 Olympic Drive
Athens, GA 30601 USA
Tel: 706-357-7223
Fax: 706-355-5435

Central America and Mexico
Ejercito Nacional 253-A Piso 5
Colonia Anahuac
11320 Mexico D.F.
Ph: (5255) 5531-5010
Fax: (5255) 5531-5010 ext.1005

A member of the United Technologies Corporation family. Stock symbol UTX.

©2012 UTC Climate | Controls | Security. Printed in USA 0912.



Printed with 10% post-consumer waste recycled paper.



Climate | Controls | Security

Carrier Transicold Division
Truck/Trailer Products Group
P.O. Box 4805
Syracuse, NY 13221 USA

www.trucktrailer.carrier.com