





MEET THE NEW SUPRA® - AND THE NEW STANDARD.

See what's new with the next generation of the truck refrigeration units known for decades for performance and dependability.



PERFORMANCE SPECIFICATIONS



Supra° **S7 Unit.** Confidently transport perishable and frozen food via medium-sized trucks with the Supra S7 unit. With first-in-class architecture and a high-efficiency design that looks great on the road, it's the perfect way to add value to fleets of all sizes.

Lower Cost of Ownership. By reducing the number of mechanical components and with fewer parts overall, we've eliminated many maintenance items that can cause extended downtime and repair costs.

Intelligent Controls. APX[™] Control System — as seen on the Carrier Transicold X4 and Vector[™] platforms — provides the ideal balance of temperature control, fuel management and remarkable control intelligence to maintain an ideal environment inside the truck.

Expert Service and Support. With 180 dealer locations across North America and 24/7 service access, help is never out of reach.

Condenser Dimensions

75.4" x 32.1" x 24.2" (1,914 x 815 x 615 mm)

Evaporator Dimensions

48.2" x 21.7" x 11.4" (1,225 x 550 x 290 mm)

Body Opening

49.0" x 12.2" (1,245 x 310 mm)

Approximate Weight

TDB-57: 860 lb (390 kg) without standby TDS-57: 955 lb (434 kg) with electric standby

Evaporator Airflow

1,500 cfm (2,548 m³/hr)

Cooling Capacity

Evaporator Return Air Temp.	Diesel Operation		Standby Operation	
	BTU/hr	Watts	BTU/hr	Watts
35°F (2°C) 0°F (-18°C) -20°F (-29°C)	19,000 12,000 6,000	5,568 3,517 1,758	19,000 11,500 6,000	5,568 3,370 1,758

Ambient at 100°F (38°C)

Speed: 2,000 rpm diesel/60Hz electric standby operation

Standard Features Include:

Tier 4 Final D-722 smart diesel engine, 3 cylinder Electronic controls High-power 110-amp alternator ESI (Extended Service Interval) package 2,000-hour service interval Multistage, synthetic media oil filter Water-separating fuel filter Heavy-duty, low-noise dry air cleaner Extended-life coolant

05K12, 2-cylinder compressor 12.2 in³ displacement

Refrigerant R-452A, 6.6 lb (3 kg) High-efficiency refrigeration system

Electronic suction modulation valve
Brazed plate heat exchanger
Automatic start/stop fuel saver
Three-way refrigeration valve system
High-efficiency microchannel condenser
Maintenance-free electric condenser fan

Maintenance-free electric condenser fan Maintenance-free evaporator fan motors Automatic hot-gas heating system APX Control System

Data recorder

Automated pretrip with componentlevel fault detection

On-board diagnostics with visual indicator and audible alarm

Setpoint and operating mode locking Smart door switch logic

Programmable FreshProtect perishable protection system

City speed control (quieter operation)

Standard Features (continued):

Automatic defrost control

 $\mathsf{Cab}\;\mathsf{Command}^{\scriptscriptstyle{\mathsf{TM}}}\;\mathsf{Controller}$

Intuitive controls

Digital readout

Setpoint/operating mode

Supply air temperature

Ambient temperature

Hour meters (switch on, diesel, standby, maintenance)

Top grille Bottom panel Installation package

Accessories and Options:

Lynx Fleet[™] telematics platform DataTrak[™] 460V/3ph/60Hz electric standby

Electric standby standard with model TDS-57

208V/230V/3ph/60Hz

Battery box (separate from truck)

30-gallon fuel tank (center fill or end fill)

50-gallon fuel tank

Remote temperature sensor

Open door shutdown switch

Fuel sensor

 $\mathsf{Stealth}^{\scriptscriptstyle\mathsf{TM}}\,\mathsf{Noise}\,\mathsf{Reduction}$

Auxiliary heat systems

Fuel heater

Remote light bar

Snow/rain cover

Oil drain adapter

Specifications are subject to change without notice.

Warranty: Product warranty and limitations are outlined in Form 62-12102.

This warranty is applicable only in North America. Consult your Carrier Transicold representative for warranty coverage elsewhere. Form 62-12104. Rev E

North America

Carrier Transicold 700 Olympic Drive Athens, GA 30601 USA

Central America and Mexico

Carrier Transicold Ejercito Nacional 253-A Piso 5 Colonia Anahuac 11320 Mexico D.F.

