





HEROIC POWER AND RELIABILITY. UPGRADED.

Meet the sequel to one of the most trusted names in truck refrigeration units. The new Supra[®] unit is redesigned and revamped for greater performance and greater control.





Condenser Dimensions

75.4" x 32.1" x 24.2" (1,914 x 815 x 615 mm)

Evaporator Dimensions

48.2" x 21.7" x 11.4" (1,225 x 550 x 290 mm)

Body Opening 49.0" x 12.2" (1,245 x 310 mm)

Approximate Weight

TDB-59: 908 lb (413 kg) without standby TDS-59: 1,015 lb (460 kg) with electric standby

Evaporator Airflow

1,500 cfm (2,548 m³/hr)

Cooling Capacity

Evaporator Return Air Temp.	Diesel Operation		Standby Operation	
	BTU/hr	Watts	BTU/hr	Watts
35°F (2°C) 0°F (-18°C) -20°F (-29°C)	24,000 18,500 11,500	7,034 5,422 3,370	23,500 17,500 10,000	6,887 5,129 2,931

Ambient at 100°F (38°C)

Speed: 2,100 rpm diesel/60Hz electric standby operation

PERFORMANCE SPECIFICATIONS

Supra^{*} **S9 Unit.** Explore a unit engineered for the reliable transport of perishable and frozen food in large-sized trucks. The Supra S9 unit builds on a legacy 20 years in the making with an innovative new design, superior capacity and performance you can count on.

Proven Reliability. The Supra S9 unit provides higher capacity, faster pulldown and a smarter, high-efficiency platform that ensures dependability and peace of mind.

Intelligent Operation. APX[™] Control System combines remarkable control intelligence, temperature control and system reliability with amazingly simple operation.

Quality Engineering. By streamlining the design and using fewer mechanical components, we've extended the service interval to 2,000 hours, increased the overall lifespan and greatly reduced total operating costs.

Expert Service and Support. With 180 dealer locations across North America and 24/7 service access, help is never out of reach.

Standard Features Include:

Tier 4 Final D-722 smart diesel engine, 3 cvlinder Electronic controls High-power 110-amp alternator ESI (Extended Service Interval) package 2,000-hour service interval Multistage, synthetic media oil filter Water-separating fuel filter Heavy-duty, low-noise dry air cleaner Extended-life coolant 05K24, 4-cylinder compressor 24.4 in³ displacement Refrigerant R-452A, 7.1 lb (3.2 kg) High-efficiency refrigeration system Electronic suction modulation valve Brazed plate heat exchanger Automatic start/stop fuel saver Three-way refrigeration valve system High-efficiency microchannel condenser Maintenance-free electric condenser fan Maintenance-free evaporator fan motors Automatic hot-gas heating system APX Control System Data recorder Automated pretrip with componentlevel fault detection On-board diagnostics with visual indicator and audible alarm Setpoint and operating mode locking Smart door switch logic Programmable FreshProtect

perishable protection system City speed control (quieter operation)

Standard Features (continued):

Automatic defrost control Cab Command" Controller Intuitive controls Digital readout Setpoint/operating mode Supply air temperature Ambient temperature Hour meters (switch on, diesel, standby, maintenance) Top grille Bottom panel Installation package

Accessories and Options:

Lynx Fleet[™] telematics platform DataTrak[®] 460V/3ph/60Hz electric standby Electric standby standard with model TDS-59 208V/230V/3ph/60Hz Battery box (separate from truck) 30-gallon fuel tank (center fill or end fill) 50-gallon fuel tank Remote temperature sensor Open door shutdown switch Fuel sensor Stealth[™] Noise Reduction Auxiliary heat systems Fuel heater Remote light bar Snow/rain cover Oil drain adapter

Specifications are subject to change without notice. Warranty: Product warranty and limitations are outlined in Form 62-12102. This warranty is applicable only in North America. Consult your Carrier Transicold representative for warranty coverage elsewhere. Form: 62-12136. Rev E.

North America

Carrier Transicold 700 Olympic Drive Athens, GA 30601 USA Central America and Mexico Carrier Transicold Ejercito Nacional 253-A Piso 5 Colonia Anahuac 11320 Mexico D.F.

©2023 Carrier. All Rights Reserved. Printed in USA 01/23. Carrier, Transicold and Supra are registered trademarks of Carrier Corporation.



www.trucktrailer.carrier.com