


Carrier **X<sup>2</sup>** 2100A



*Exceptional temperature control with a new dimension in performance.*

# PERFORMANCE SPECIFICATIONS

## 2100A



2100A shown with chrome grille/stainless latch option

### Condenser Dimensions

76.4" x 85.7" x 22.8"  
(1,940 x 2,176 x 579 mm)

### Evaporator Dimensions

66.3" x 45.2" x 8.2"  
(1,684 x 1,149 x 280 mm)

### Body Opening

66.8" x 46.0"  
(1,696 x 1,168 mm)

### Approximate Weight

2100A: 1,640 lb. (744 kg)  
Remote 50-gal. aluminum fuel tank: 65 lb. (29 kg)  
Battery: 50 lb. (23 kg)

Cooling/Temperature Capacity:  
Ambient at 100°F (38°C)  
Speed: 1,700 rpm diesel

| Evaporator<br>Return<br>Air Temp. | Diesel Operation |        |
|-----------------------------------|------------------|--------|
|                                   | Btuh             | Watts  |
| 35°F ( 2°C)                       | 64,000           | 18,760 |
| 0°F (-18°C)                       | 33,000           | 9,670  |
| -20°F (-29°C)                     | 21,000           | 6,155  |

**X2 Series** builds upon the world standard durability, reliability, performance, and economy of the original X Series.

- **Lower lifecycle cost** with Advance™ controller, Extended Service Interval (ESI™) components, advanced diagnostics, and a fast, thorough pretrip.
- **Durable, rugged construction** includes a proven engine, compressor, microprocessor controller, and components that hold up to the rigors of distribution and long-haul operations.

### Standard Features Include:

CT4-134DI diesel engine  
2.2 liter direct-injection  
4 cylinders  
15 qt. (14.2 liter) oil capacity  
05G-41CFM compressor  
41 CFM displacement  
6 cylinders  
High capacity oil pump  
Refrigerant R-404A  
UltraFresh 3™ temperature control  
Electronic stepper valve  
Automatic Start/Stop fuel saver  
High-power 65-amp alternator  
Remote aluminum fuel tank  
50-gal. single-fill – 22"  
Durashell 2™ composite doors  
Single latch release  
Automatic hot gas heating system  
Pressurized coolant system  
Automatic defrost control  
TurboAir™ management system  
Screw-post battery terminals  
Advance™ microprocessor  
Datalink™ data recorder  
MessageCenter™ display  
Multilingual display  
Advanced pretrip and diagnostics  
PCMCIA card interface  
ESI™ (Extended Service Interval) package  
Multistage, synthetic media oil filter  
Water-separating fuel filter  
Heavy-duty, low-noise dry air cleaner  
Extended-life antifreeze  
Installation package

- **Lower noise levels** and better sound quality are acoustically engineered into the design. The Stealth™ option offers exceptionally quiet operation for noise-sensitive environments.
- **Exceptional capacity and airflow** offer dependability, superior temperature control, and multi-application flexibility.
- **Modern aerodynamic design** features damage and dirt-resistant doors manufactured from a high-strength, colorfast composite.

### Accessories and Options:

DataTrak™ remote communications  
Open trailer door indicator and shutdown switches  
Fuel heater  
Synthetic engine oil  
Evaporator drain line extensions  
Silicone hoses  
Remote light bar  
Remote temperature probe  
Stealth 2™ noise reduction package  
Stud-post battery terminals  
Unit impact protection bumpers  
Microprocessor impact protection bumper  
High-power 105-amp alternator  
Extra-heavy-duty suction side fuel filter  
Fuel tank level and shutdown sensor  
Door locks  
Chrome grille/stainless latch package  
Custom color paint  
Condenser bug/hail screen  
AutoFresh™ air exchange  
IntelliSet™ with ProductShield™  
Flush mount remote control panel  
Remote aluminum fuel tanks:  
30-gal. or 50-gal. single-fill – 18"  
30-gal. or 75-gal. single-fill – 22"  
100-gal. single- or double-fill – 22"  
120-gal. single- or double-fill – 22"

 **2100A**



**North America**  
Carrier Transicold  
700 Olympic Drive  
Athens, GA 30601 USA  
Tel: 706-357-7223  
Fax: 706-355-5435

**Mexico and Central America**  
Ejercito Nacional No. 418  
Piso 9, Torre Yumal  
Col. Chapultepec Morales  
11570 Mexico, D.F.  
Tel: (5255) 9126-0300  
Fax: (5255) 9126-0383



**Carrier**

A United Technologies Company

Carrier Transicold Division  
Carrier Corporation  
Truck/Trailer Products Group  
P.O. Box 4805  
Syracuse, NY 13221 USA

[www.trucktrailer.carrier.com](http://www.trucktrailer.carrier.com)