









# 7500 PERFORMANCE SPECIFICATIONS



#### **Condenser Dimensions**

76.4" x 85.7" x 22.8" (1,940 x 2,176 x 579 mm)

#### **Evaporator Dimensions**

66.3" x 45.2" x 8.2" (1,684 x 1,149 x 280 mm)

### **Body Opening**

66.8" x 46.0" (1,696 x 1,168 mm)

# **Approximate Weight**

1,690 lb. (767 kg)
Remote 50 gallon aluminum fuel tank with mounting brackets: 65 lb. (29 kg)
Battery: 50 lb. (23 kg)

## **Cooling Capacity:**

Ambient at 100°F (38°C)

Evaporator Return Air Temp.	High Speed Diesel Operation	
	BTU/hr	Watts
35°F ( 2°C) 0°F (-18°C) -20°F (-29°C)	68,000 37,000 25,000	19,930 10,845 7,330

# **Evaporator Airflow**

Applied system performance: 3,050 cfm (5,180 m³/hr)

**The X4™ Series.** Built upon the proven X2™ platform, the X4 7500 unit sets the bar even higher as the new industry standard for refrigeration performance and efficiency.

**Ultra high capacity.** The model 7500 establishes the benchmark for extreme performance. It delivers fast pulldown, precise temperature control and peace of mind for the most demanding applications.

**Ultra high efficiency.** ecoFORWARD™ technologies deliver significant fuel savings as well as higher performance, lower operating costs and compliance with 2013 EPA emissions regulations.

#### Standard Features Include:

Tier 4 Final V2203L smart diesel engine 4 cylinder 2.2 liter direct-injection 24.8 HP (18.5kW) at 1,800 RPM high speed

CAN bus electronic interface 15 qt. (14.2 liter) oil capacity High power 70 amp alternator ESI™ (Extended Service Interval) package

3,000 hour service interval Multistage, synthetic media oil filter Water separating fuel filter

Heavy duty, low noise dry air cleaner Extended life coolant

05G 41CFM compressor 40 in³ displacement

6 cylinders

Refrigerant R-404A, 16.5 lb (7.5 kg) UltraFresh 3™ temperature control

TRU-Demand™ high energy efficiency Electronic expansion valve Electronic suction modulation Compressor unloaders

Brazed plate heat exchanger

Automatic start/stop fuel saver Automatic hot gas heating system APX™ Control System

Integrated USB port

IntelliSet™ with ProductShield™
DataLink™ data recorder
Information dashboard
Multilingual graphical display
Pretrip and Virtual Tech diagnostics

CONTROL SYSTEM

**Proven reliability.** The enhanced platform now includes proven high efficiency components from our Vector™ series and an industry-leading warranty for dependability and peace of mind.

**APX**<sup>™</sup> **control system.** The modular APX system combines remarkable control intelligence, temperature control and system reliability with amazingly simple operation.

**Lower cost of ownership.** Combining innovative engineering with a straightforward, practical design means less fuel consumption, reduced engine run hours and lower maintenance costs.

# Standard Features (continued):

High efficiency microchannel condenser
V-Force™ vortex suppression fan
TurboAir™ evaporator management
Composite doors with single-latch release
Installation package
Screw post battery terminals
Remote aluminum fuel tank
50 gal. single fill, 22"
Remote light bar
Full bottom panel

# **Accessories and Options:**

eSolutions $^{\text{\tiny TM}}$  telematics system for remote monitoring and control DataTrak™ remote communications Open trailer door indicator and shutdown switches Fuel heater Evaporator drain line extensions Premium ECR hoses APX Remote Control Panel Remote temperature probes Stealth™ 2 noise reduction package Unit impact protection bumpers High power 105 amp alternator Extra heavy duty suction side fuel filter Fuel tank level and shutdown sensor Chrome grille/stainless latch package Refrigerant R-452A, 16.5 lb. (7.5 kg)

Remote aluminum fuel tanks: 30 gal. or 75 gal. single fill, 22" 100 gal. single or double fill, 22" 120 gal. single or double fill, 22"

AutoFresh™ air exchange

Specifications are subject to change without notice.

Warranty: Product warranty and limitations are outlined in Form 62-11669.

This warranty is applicable only in North America. Consult your Carrier Transicold representative for warranty coverage elsewhere. Form 62-11662 Rev I.

North America Carrier Transicold 700 Olympic Drive Athens, GA 30601 USA Central America and Mexico Carrier Transicold Ejercito Nacional 253-A Piso 5 Colonia Anahuac 11320 Mexico D.F.



